



VGLORY[®]
Engineered In Holland

BIAS TYRES



www.vglorygroup.nl



VG-M2

L-3/E-3 GENERAL BLOCK(STREAD)
 普通花纹块工程机械轮胎

Specially desinged for cut and heat resistant compound.
 Regular type of tread pattern suitable for hard rock surface
 and haulage service.



VG-HDT

NEW L-3/E-3 LOADER MASTER(ZTREAD)
 Z 型块状工程机械轮胎

NewZ treadtyre for lowintensity applicationof Loader/
 Earthmover/Grader



VG-MX

L-3/E-3 PREMIUM DESIGN OTR TYRE
 高档设计工程机械轮胎

Block non-directional pattern design,
 Excellent holding and traction performance With good
 controllability.

工业叉车轮胎

INDUSTRIAL FORKLIFT TIRE



FORKLIFT I



- 1) 特殊的配方设计使轮胎具有良好的抗切割及耐磨性能
- 2) 特殊的花纹设计可赋予轮胎优良的抓着力

FORKLIFT I

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD(Kg)		类型 TYPE
						驱动轮 DRIVE	转向轮 STEER	
4.00-8	8	423	108	2.50C	960	782		TT
5.00-8	10	469	131	3.00D	1000	950		TT
6.00-9	10	545	160	4.00E	860	1515	1280	TT
6.50-10	12	597	178	5.00F	970	1935	1635	TT
7.00-12	12	683	192	5.00S	860	2445	2065	TT
7.00-15	12	762	203	6.00	860	2835	2395	TT
7.50-15	12	808	215	6.00G	790	3140	2650	TT
7.50-16	16	834	215	6.00G	950	3225		TT
8.25-15	14	847	236	6.50BD	830	3830	3235	TT
9.00-20	14	1038	259	7.00	760	4425		TT
10.00-20	16	1073	278	7.50	790	5140		TT
11.00-20	16	1104	293	8.00	760	5460		TT
12.00-20	18	1146	315	8.50	790	4670		TT
12.00-20	20	1146	315	8.50	890	6874		TT
12.00-24	20	1250	270	8.5	1000	7500		TT
14.00-24	28	1368	375	10.00	1000	9500		TT
18X7-8	16	465	168	4.33R	1030	2280	1925	TT
21X8-9	14	533	203	6.00E	1000	2115	1785	TT
23X9-10	16	584	229	7.00	1030	2720	2305	TT
23X10-12	20	597	250	8.00G	1000	3750	2900	TT
27X10-12	18	682	254	8.00G	1030	3355	2835	TT
28X9-15	14	706	221	7.00BD	970	3075	2595	TT
32X12.1-15	24	826	305	9.75	1030	4240	4240	TT
250-15	16	735	250	7.50BD	930	3855	3265	TT
300-15	20	840	300	8.00BD	930	5940	4990	TT

FORKLIFT II



FORKLIFT III



FORKLIFT IV



FORKLIFT II

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD(Kg)		类型 TYPE
						驱动轮 DRIVE	转向轮 STEER	
6.00-9	10	545	160	4.00E	860	1515	1280	TT
6.50-10	10	597	178	5.00F	790	1725	1455	TT
7.00-12	12	683	192	5.00S	860	2445	2065	TT
7.00-15	12	762	203	6.00	860	2835	2395	TT
8.25-15	14	847	236	6.50BD	830	3830	3235	TT
28X9-15	14	706	221	7.00BD	970	3075	2595	TT

FORKLIFT III

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD(Kg)		类型 TYPE
						驱动轮 DRIVE	转向轮 STEER	
5.00-8	10	469	131	3.00D	1000		950	TT
6.00-9	12	545	160	4.00E	1030	1685	1425	TT
6.50-10	10	597	178	5.00F	790	1725	1455	TT
7.00-12	12	683	192	5.00S	860	2445	2065	TT
8.25-15	14	847	236	6.50BD	830	3830	3235	TT
18x7-8	16	465	168	4.33R	1030	2280	1925	TT
28X9-15	14	706	221	7.00BD	970	3075	2595	TT
250-15	16	735	250	7.50BD	930	3855	3265	TT
300-15	20	840	300	8.00BD	930	5940	4990	TT

FORKLIFT IV

规格 SIZE	层级 PR	标准轮辋 STANDARD RIM	断面宽(mm) SECTION WIDTH	外直径(mm) SECTION WIDTH	花纹深度(mm) PATTERN DEPTH	负荷 (Kg)	气压 (Kpa)	最高 时速 (km/h)	速度 级别 SPEED LEVEL
5.00-8	10	3.50D	137	470	13	1150	1000	25	A5
6.00-9	10	4.00E	160	545	13	1795	850	25	A5
6.50-10	10	5.00F	178	597	15	1865	775	25	A5
7.00-12	12	5.00S	192	683	15	2830	850	25	A5
7.00-9	10	5.00S	192	590	13	2365	850	25	A5
8.25-12	12	6.5	235	765	16	3750	750	25	A5
8.25-15	14	6.5	235	840	17	3000	950	25	A5
28X9-15	14	7.0	221	706	14.5	3075	970	25	A5

工程机械轮胎

CONSTRUCTION MACHINERY TIRE



G-2



VG-M2



G-2

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
13.00-24	12	1278	333	8.00	300	2725	TL
14.00-24	12	1247	362	8.00	250	3075	TL

VG-M2

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	速度10KM/H		速度50KM/H		类型 TYPE
					气压(Kpa) PRESSURE	负荷(Kg) LOAD	气压(Kpa) PRESSURE	负荷(Kg) LOAD	
14.5-16	14	950	340	10.0	280	1800	280	1450	TT
16/70-20	14	1075	410	13	450	5150	350	2925	TT
16/70-24	14	1175	410	13	450	5650	350	3375	TT
17.5-25	16	1350	445	14.00	475	7300	300	4250	TT
20.5-25	16	1490	520	17.00	350	8250	275	5450	TT
20.5-25	20	1490	520	17.00	450	9500	325	6000	TT
23.5-25	20	1615	595	19.5	375	10900	300	7300	TT
23.5-25	24	1615	595	19.5	475	12500	350	8000	TT

R-1



R-1

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
7-14	6	691	183	6.00	250	450	TL
7-16	6	742	183	6.00	250	500	TL
8-16	6	790	211	6.00	190	615	TL
8.3-16	6	790	211	7.00	230	545	TL
9.5-16	6	845	241	8.00	210	630	TL
11.2-24	4	1103	284	10.00	120	750	TL
11.2-24	6	1103	284	10.00	180	950	TL
12.5-15	4	825	318	10.00	210	1120	TL

I-1

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
7.60-15	8	740	176	5.50	390	710	TL
9.5L-15	8	767	241	7.00	300	1120	TL
10-15	8	780	280	8.00	280	1070	TL
11L-15	10	777	279	8.00	300	1320	TL
12.5L-15	10	823	318	10.00	300	1550	TL
16.5L-16.1SL	10	800	354	10.00	310	1180	TL
31X13.50-15	8	1024	419	W14C	250	2360	TL

F3-1

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
11L-15	10	777	279	8.00	300	1320	TL
11L-16	10	803	279	8.00	300	1360	TL

I-1



F3-1



R-3



R-3

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
31X13.50-15	12	782	351	10.00	520	1600	TL

F3-2

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
11L-16	10	803	279	8.00	300	1360	TL
14.5-16.1	10	940	373	11.00	280	1450	TL

F-2M

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
6.0-16	6	712	159	4.00	340	560	TL
9.5L-15	8	777	241	7.00	300	690	TL

N707

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
12.5/80-18	10	991	308	9.00	310	2430	TL


I-3

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
15.5/80-24	12	1266	400	12.00	310	2900	TL
31X15.50-15	10	810	401	12.00	380	2215	TL

L-3S/L-4S



L- 4S/L-5S



C-1



滑移装载机轮胎

SKID STEER LOADER TIRE

L-3S/L-4S

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10.00-20	14	1055	278	7.5	670	4250	TT

L- 4S/L-5S

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
12.00-24	16	1245	315	8.5	675	6150	TT
12.00-24	20	1245	315	8.5	825	6900	TT
12.00-24	24	1245	315	8.5	975	7750	TT
14.00-24	24	1370	375	10.00	850	9500	TT
17.5-25	20	1350	445	14.00	575	8250	TT
18.00-25	40	1615	495	13.00	950	17000	TT

C-1

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
7.50-15	6	808	215	6.00	400	1850	TT
7.50-15	12	808	215	6.00	750	2650	TT
7.50-15	14	808	215	6.00	875	2900	TT
13/80-20	18	1048	326	8.00	900	5000	TT



SLID I



SLID II



- 1) 特殊形式的轮辋保护设计
- 2) 良好的导向性能和牵引性能
- 3) 开放式的花纹设计提供良好的自洁性能

SLID I

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
5.70-12	6	570	146	4.5	520	750	TL
7.00-15	8	765	200	6.0	410	4150	TL
10-16.5	10	773	264	8.25	520	2135	TL
12-16.5	12	831	307	9.75	550	2865	TL
14-17.5	14	921	349	10.50	550	3875	TL
15-19.5	14	1019	389	11.75	485	4565	TL
23x8.50-12	8	592	213	7.00	450	975	TL
27x8.50-15	8	680.7	213.4	7LB	410	825	TL
27x10-12	8	701	264	8LB	410	898	TL
27x10.50-16.5	8	685.5	261.6	8LB	410	898	TL
31x15.50-15	8	792	391	13LB	310	1250	TL
33x15.50-16.5	14	830.6	388.6	12.00	410	3100	TL

SLID II

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD(Kg)		类型 TYPE
						驱动轮 DRIVE	转向轮 STEER	
10-16.5	8	773	264	8.25	410	1880		TL
12-16.5	10	831	307	9.75	450	2540		TL
12.5/80-18	10	965	308	9.00	310	1700	2430	TL
14-17.5	10	921	349	10.50	380	3150		TL
15-19.5	4	1019	389	11.75	140	2250		TL
15-19.5	6	1019	389	11.75	210	2780		TL
18x8.50-8	4	455	218	7.0	150	375		TL
20x10-10	4	511	254	8.0	150	530		TL
25x8.50-14	4	651	217	7.00	240	785		TL
25x8.50-14	6	651	217	7.00	340	965		TL
27x8.50-15	6	685	215	7.00	310	710		TL
43x16.00-20	4	1078	406	14.00	140	1420		TL

SLID III



SLID IV



SLID V



SLID VI



SLID III

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD(Kg)		类型 TYPE
						驱动轮 DRIVE	转向轮 STEER	
10-16.5	8	773	264	8.25	410	1880		TL
12-16.5	10	831	307	9.75	450	2540		TL
12.5/80-18	10	991	307.5	9.00	310	1700	2430	TL
12.5/80-18	14	991	307.5	9.00	430	2120	3000	TL
14-17.5	10	932	356	10.5	380	3105		TL
14-17.5	14	932	356	10.5	550	3875		TL
15-19.5	14	983	398	11.75	485	4565		TL

SLID IV

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	8	773	264	8.25	410	1880	TL
12-16.5	10	831	307	9.75	450	2540	TL

SLID V

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	8	773	264	8.25	410	1880	TL
12-16.5	10	831	307	9.75	450	2540	TL

SLID VI

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	8	773	264	8.25	410	1880	TL
12-16.5	10	831	307	9.75	450	2540	TL



SLID VII

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	12	773	264	8.25	620	2735	TL
12-16.5	14	831	264	9.75	620	3075	TL

SLID VIII

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	14	790	268	8.25	520	2135	TL
12-16.5	12	836	315	9.75	550	2865	TL
14-17.5	14	932	358	10.50	550	3875	TL

SLID IX

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	10	790	268	8.25	520	2135	TL
12-16.5	12	835	307	9.75	550	2865	TL
14-17.5	14	935	349	10.50	550	3875	TL
12.5/80-18	14	965	308	W9	425	3625	TL
12.5/80-18	16	965	308	W9	490	3940	TL
16.9-28	14	1410	450	W15	300	4840	TL
23X8.50-12	8	574	213	7.00	450	975	TL
27X8.50-15	10	681	215	7LB	520	1500	TL

SLID X

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	8	773	264	8.25	410	1880	TL
12-16.5	10	831	307	9.75	450	2540	TL

SLID XI



SLID XI

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
15-19.5	6	1019	389	11.75	210	2780	TL
25X8.50-14	6	640	226	7.00	340	965	TL
445/50D710	18	1202	461	15.00	590	7300	TL

SLID XII

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
18X8.50-8	4	455	218	7.0	150	375	TL
27X8.5-15	6	678	215	7.00	310	710	TL
33X15.50-16.5	10	841	408	12.00	210	2270	TL
41X14.00-20	4	1070	365	11.00	170	1400	TL
26X12.00-12	4	648	307	10.5	140	800	TL

SLID XIII

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
10-16.5	8	773	264	8.25	410	1880	TL
12-16.5	10	831	307	9.75	450	2540	TL

SLID XIV

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
14-17.5LT	10	907	349	10.5	590	2500	TL

矿山专用轮胎

MINE TIRE



M-TRUCK III M-TRUCK IV M-TRUCK V M-TRUCK VI M-TRUCK VII



M-TRUCK III

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
6.50-16	14	785	200	5.50F	730		1320	1180	16.5
7.00-16	14	785	200	5.50F	730		1320	1180	16.5
7.50-16	14	816	215	6.00G	730		1500	1320	17.5
8.25-16	14	867	235	6.50H	630		1700	1500	18
10.00-20	16	1073	278	7.5	810	740	3000	2650	28
11.00-20	18	1105	293	8.0	910	840	3650	3150	28

M-TRUCK IV

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
7.00-16	14	785	200	5.50F	730		1320	1180	21
7.50-16	14	816	215	6.00G	730		1500	1320	22
8.25-16	14	867	235	6.50H	630		1700	1500	23

M-TRUCK V

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
14.00-20	20	1265	375	10.0	770	700	5000	4375	25
14.00-20	24	1265	375	10.0	870	810	6800	6200	25

M-TRUCK VI

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
11.00-20	18	1105	295	8.0	910	840	3650	3150	24
12.00-20	18	1145	315	8.5	810	740	3750	3350	26

M-TRUCK VII

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
9.00-20	16	1038	259	7.0	880	810	2900	2500	21
11.00-20	18	1105	293	8.0	910	840	3650	3150	21
12.00-20	18	1145	315	8.5	810	740	3750	3350	22
12.00-24	18	1247	315	8.5	810	740	4250	3750	22

矿山专用轮胎/矿车专用轮胎

VG-MX



M-TRUCK I



M-TRUCK II



VG-MX

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
11.00-20	18	1105	293	8.0	910	840	3650	3150	25
12.00-20	20	1145	315	8.5	880	810	4000	3450	25
14.00-20	24	1265	375	10.0	870	810	6800	6200	25
13.00-25	28	1300	350	8.5	740		5570		26
14.00-24	32	1370	375	10.0	1000		10600		28
14.00-25	36	1370	375	10.0	1050		11200		28

M-TRUCK I

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
9.00-20	16	1018	259	7.0	880	810	2900	2500	28
10.00-20	16	1073	278	7.5	810	740	3000	2650	25
11.00-20	18	1105	293	8.0	910	840	3650	3150	28
12.00-20	18	1145	315	8.5	810	740	3750	3350	28

M-TRUCK II

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL	
6.00-13	8	655	170	4.50B	420		650	580	10.5
6.50-16	12	750	185	5.50F	630		1060	925	13
7.00-16	14	785	200	5.50F	730		1320	1180	14
7.50-16	14	816	215	6.00G	730		1500	1320	14
7.50-16	16	816	215	6.00G	770		1600	1450	14
8.25-16	16	867	235	6.50H	730		1800	1600	15
9.00-20	16	1018	259	7.0	880	810	2900	2500	18
10.00-20	16	1055	278	7.5	810	740	3000	2650	19
11.00-20	18	1085	293	8.0	910	840	3650	3150	20
12.00-20	18	1125	315	8.5	810	740	3750	3350	20

挖掘机轮胎

EXCAVATOR TIRE



EXCAVATE I



EXCAVATE II



EXCAVATE I

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
8.25-20	14	962	230	6.5	680	1501	TT
9.00-20	14	1018	259	7.00	700	2500	TT
10.00-20	16	1050	275	7.50V	750	2917	TT
11.00-20	12	1082	290	8.00V	620	2574	TL
11.00-20	16	1082	290	8.00V	725	3152	TT

EXCAVATE II

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
7.50-16	14	805	215	6.00G	730	1500	TT
8.25-16	16	855	235	6.50H	730	1800	TT



MOTOR I

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
7-14.5	12	677	185	6.00	690	1060	TL
8-14.5	12	707	203	6.00	690	1285	TL

MOTOR II

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
8-14.5	12	707	203	6.00	690	1285	TL

MOTOR III

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
8-14.5	12	707	203	6.00	690	1285	TL
9-14.5	12	711	241	7.00	690	1500	TL

MOTOR IV

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
8-14.5	14	725	213	6.00	790	1400	TL
9-14.5	14	730	242	7.00	790	1600	TL

载重汽车轮胎

TRUCK TIRE



- 1) 卓越的高速性能
- 2) 特殊的花纹设计, 提供了良好的抓着性能
- 3) 防侧滑性能优越

TRAILER I

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD
4.80-8	4	423	121	3.75	410	265
4.80-8	6	423	121	3.75	620	345
4.80-12	4	524	121	3.75	410	355
4.80-12	6	524	121	3.75	620	450
5.70-8	4	469	146	4.50	340	325
5.70-8	6	469	146	4.50	520	412
5.30-12	4	548	135	4.25	380	387
5.30-12	6	548	135	4.25	550	475

TRAILER II

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负 荷LOAD(Kg)	
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL
10.00-20	14	1055	278	7.5	700	630	2800	2430
11-22.5	12	1054	279	8.25	590	620	2500	2180

TRAILER III

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa)	负 荷(Kg)
ST175/80D13	6	177	610	5.00	350	615
ST205/75D14	6	203	664	5.50	350	800
ST205/75D15	6	203	689	5.50	350	825
ST225/75D15	6	223	719	6.00	350	975



TRAILER IV

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)	
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL
9.00-20	16	1018	259	7.0	880	810	2900	2500
10.00-20	16	1055	278	7.5	810	740	3000	2650
11.00-20	18	1085	293	8.0	910	840	3650	3150
12.00-20	18	1125	315	8.5	810	740	3750	3350

TRAILER V

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)	
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL
9.00-20	16	1018	259	7.0	880	810	2900	2500
10.00-20	16	1055	278	7.5	810	740	3000	2650
11.00-20	18	1085	293	8.0	910	840	3650	3150
12.00-20	18	1125	315	8.5	810	740	3750	3350

TRAILER VI

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)	
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL
11.00-20	18	1018	293	8.0	910	840	3650	3150
12.00-20	18	1125	315	8.5	810	740	3750	3350



TRUCK I

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD(Kg)		花纹深度 (mm) TREAD DEPTH
						单胎 SINGLE	双胎 DUAL	
6.50-16	12	761	185	5.50F	630	1060	925	13
7.00-16	14	785	200	5.50F	730	1320	1180	14
7.50-16	14	816	215	6.00G	730	1500	1320	14
7.50-16	16	816	215	6.00G	770	1600	1450	14
8.25-16	16	867	235	6.50H	730	1800	1600	15

TRUCK II;TRUCK III; TRUCK IV ;TRUCK V ;TRUCK VI

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负荷LOAD(Kg)	
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL
6.00-13	8	655	170	4.50B	420		650	580
6.00-14	8	691	170	4(1/2)J	420		690	600
6.50-14	8	717	180	4(1/2)J	420		775	690
6.50-16	12	761	185	5.50F	630		1060	925
6.50-15	10	730	180	4.50E	530		950	825
7.00-16	14	785	200	5.50F	730		1320	1180
7.00-15	12	750	200	5.50F	630		1150	1030
7.50-16	14	816	215	6.00G	730		1500	1320
8.25-16	14	867	235	6.50H	630		1700	1500
8.25-20	14	974	236	6.5	850	740	240	1950
9.00-20	16	1038	259	7.0	880	810	2900	2500
10.00-20	16	1073	278	7.5	810	740	3000	2650
11.00-20	16	1105	293	8.0	810	740	3350	2900
12.00-20	18	1145	315	8.5	810	740	3750	3350

TRUCK VII



TRUCK VIII



农业专用轮胎

AGRICULTURAL FETUS

TRUCK VII

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压PRESSURE(Kpa)		负 荷LOAD(Kg)	
					单胎 SINGLE	双胎 DUAL	单胎 SINGLE	双胎 DUAL
7.00-16	14	785	200	5.50F	730		1320	1180
7.00-16	16	785	200	5.50F	770		1500	1320
7.50-16	14	816	215	6.00G	730		1500	1320
7.50-16	16	816	215	6.00G	770		1600	1450
8.25-16	14	867	235	6.50H	630		1700	1500
8.25-16	16	867	235	6.50H	730		1800	1600
10.00-20	16	1055	278	7.5	810	740	3000	2650
11.00-20	18	1085	293	8.0	910	840	3650	3150
12.00-20	18	1125	315	8.5	810	740	3750	3350

TRUCK VIII

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷LOAD(Kg)	
						单胎 SINGLE	双胎 DUAL
6.00-14	8	680	170	4(1/2)J	420	690	600
6.00-16	6	730	170	4.50E	420	750	670
6.50-14	8	705	180	4(1/2)J	420	775	690
6.50-16	8	750	185	5.50F	420	850	750
7.00-15	10	750	200	5.50F	530	1030	925
7.00-15	8	750	200	5.50F	420	900	800
7.00-16	8	775	200	5.50F	420	975	850
7.00-16	10	775	200	5.50F	530	1090	950
7.50-15	10	780	215	6.00G	530	1215	1060
7.50-15	12	780	215	6.00G	630	1360	1215
7.50-16	8	805	215	6.00G	420	1120	975
7.50-16	14	805	215	6.00G	730	1500	1320



R-1



R-1

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
7-14	6	691	183	6.00	250	450	TL
7-16	6	742	183	6.00	250	500	TL
8-16	6	790	211	6.00	190	615	TL
8.3-16	6	790	211	7.00	230	545	TL
9.5-16	6	845	241	8.00	210	630	TL
11.2-24	4	1103	284	10.00	120	750	TL
11.2-24	6	1103	284	10.00	180	950	TL
12.5-15	4	825	318	10.00	210	1120	TL

I-1

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
7.60-15	8	740	176	5.50	390	710	TL
9.5L-15	8	767	241	7.00	300	1120	TL
10-15	8	780	280	8.00	280	1070	TL
11L-15	10	777	279	8.00	300	1320	TL
12.5L-15	10	823	318	10.00	300	1550	TL
16.5L-16.1SL	10	800	354	10.00	310	1180	TL
31X13.50-15	8	1024	419	W14C	250	2360	TL

F3-1

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
11L-15	10	777	279	8.00	300	1320	TL
11L-16	10	803	279	8.00	300	1360	TL

I-1



F3-1



R-3



R-3

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
31X13.50-15	12	782	351	10.00	520	1600	TL

F3-2

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
11L-16	10	803	279	8.00	300	1360	TL
14.5-16.1	10	940	373	11.00	280	1450	TL

F-2M

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
6.0-16	6	712	159	4.00	340	560	TL
9.5L-15	8	777	241	7.00	300	690	TL

N707

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
12.5/80-18	10	991	308	9.00	310	2430	TL

I-3

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负 荷(Kg) LOAD	类 型 TYPE
15.5/80-24	12	1266	400	12.00	310	2900	TL
31X15.50-15	10	810	401	12.00	380	2215	TL

R-4



N710



N711



R-4

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷(Kg) LOAD	类型 TYPE
12.5/80-18	10	991	308	9.00	310	2430	TL
14.9-24	12	1231	378	W13	290	2900	TL
16.9-24	12	1309	429	W15	260	3250	TL
16.9-28	12	1410	429	W15	260	3450	TL
17.5L-24	10	1241	445	W15	220	2800	TL
18.4-24	10	1374	477	W16	250	3750	TL
19.5L-24	12	1314	495	W16	230	3450	TL
21L-24	12	1378	533	W18L	220	3875	TL
21L-24	16	1378	533	W18L	280	4500	TL

N710

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD(Kg)		类型 TYPE
						单胎 SINGLE	双胎 DUAL	
12.5/80-18	14	965	308	9.00	430	2120	3000	TL
15.0/55-17	14	850	391	13.00	360	1800	2575	TL
19.0/45-17	14	866	491	16.00	280	1950	2800	TL
400/60-15.5	10	874	404	13.00	280	1700	2430	TL
500/50-17	14	874	404	13.00	360	2000	2900	TL
500/50-17	14	933	500	16.00	275	2360	3350	TL

N711

规格 SIZE	层级 PR	外直径(mm) OVERALL DIAMETER	断面宽(mm) SECTION WIDTH	标准轮辋 STANDARD RIM	气压(Kpa) PRESSURE	负荷LOAD (Kg)	类型 TYPE
16.5L-16.1SL	10	1024	419	W14C	250	2360	TL

F-2



1) 适用于农业拖拉机的导向轮

F-2

规格 SIZE	层级 PR	标准轮辋 STANDARD RIM	断面宽(mm) SECTION WIDTH	外直径(mm) SECTION WIDTH	花纹深度(mm) PATTERN DEPTH	负荷(Kg) LOAD	气压(Kpa) PRESSURE	最高时速(Kg) Top speed	速度级别 SPEED LEVEL
4.00-14	6	3.00D	110	590	8	270	340	30	A6
4.00-16	6	3.00D	110	640	8	300	340	30	A6
5.00-15	6	4J	140	665	10	465	420	30	A6
5.50-16	6	4.00E	150	710	10	525	370	30	A6
6.00-16	6	4.00E	160	740	15	560	340	30	A6
6.50-20	6	5.00F	180	860	15	725	310	30	A6
6.50-16	6	4.5	173	761	16	560	330	30	A6
7.50-16	6	5.5	203	808	15	670	300	30	A6
10.00-16	8	8LB	274	894	26	1060	300	30	A6
11.00-16	8	10LB	315	967	29	1180	280	30	A6



OTR TYRES

Size	code
26.5-25	E-3 L-3
29.5-25	E-3 L-3
8.25-16	E-3 L-3
7.50-16	E-3 L-3
15.5-25	E-3 L-3
17.5-25	E-3 L-3
26.5-25	E-3 L-3
14.00-24	E-3 L-3
16.00-24	E-3 L-3
16/70-24	E-3 L-3
16/70-20	E-3 L-3
16/60-20	E-3 L-3
16/70-16	E-3 L-3
14/90-16	E-3 L-3
12.00-16	E-3 L-3
16.00-25	E-3 L-3
16/70-16**	E-3 L-3
20.5/70-16**	E-3 L-3
20.5/70-16	E-3 L-3

9.00-16	E-7
9.00-17	E-7
17.5-25	IND-3S
23.5-25	IND-3S
23.5-25	L-4
17.5-25	L-5
20.5-25	L-5
23.5-25	L-5
17.5-25	G-2 L-2
20.5-25	G-2 L-2
16/70-16	E-3 L-3
16.00-25	IND-3 E-3
18.00-25	IND-3 E-3
14.00-20	E-7
16.00-20	E-7
20.5/70-16	E-3 L-3
1500*600-635	E-2
23.1-26	R-3 C-2 E-7

SPECIALITY IND TYRES

Size	code
11L-16	R-4
16.9-24	R-4+
16.9-24	R-4
18.4-26	R-4
17.5L-24	R-4
9.00-20	L-2NHS
8.25-20	G-2/L-2
9.00-20	G-2/L-2
10.00-20	G-2/L-2
11.00-20	G-2/L-2
19.5L-24	L-5
12.5/80-18	R-4+
33X12-16.5	OFF Road
33X12-16.5	SANDTRACK
33X12-16.5	TURF

9.5L15	I-1
11L-15	I-1
11L-16	I-1
12.5L-15	I-1
11L-15	F-3
11L-16	F-3
21L-24	R-4
19.5L-24	R-4
19.5L-24	R-4
10.5/80-18	R-4
12.5/80-18	R-4
15.5/80-24	R-1
405/70-20	DR-4
405/70-24	DR-4
355/55D625	R-4

SUPER SOLID TYRES

Size	code
16X6-8	IND
8.25-20	IND

Size
200-8
16*6-8
406X-125

AGRICULTURAL TYRES

Size	code			
16.9-28	R-1	12.4-26	PR-1	6.00-16
18.4-34	R-1	13.6-24	PR-1	5.50-16
7.50-20	R-1	13.6-38	PR-1	5.00-16
15.5-38	R-1	14.9-26	PR-1	4.50-16
11-38	CR-1	14.9-28	PR-1	4.00-14
12.4-48	CR-1	14.9-30	PR-1	4.00-12
14.9-48	CR-1	16.9-30	PR-1	
6.50-16	R-1/HR-1	16.9-34	PR-1	
9.5-38	R-2	18.4-34	PR-1	
19.5L-24	R-2	18.4-38	PR-1	
16.9-28	R-2	16.9-28	PR-1	
18.4-30	R-2	20.8-38	PR-1	
23.1-26	R-2	4.50-16		
28L-26	R-2	5.00-14		
20.8-38	R-2	4.50-14		
12.00-18	R-1	4.00-14		
12.00-18	R-1	4.50-12		
6.00-12	PR-1	5.00-14		
6.50-16	PR-1	4.50-14		

MINING TYRES

Size
9.00-16
6.00-15

